




PRODUCT SPECIFICATION

SAGA Pendant 60

Article no: 100006



SOLUTION DESCRIPTION

PRODUCT DESCRIPTION

The BrainLit Saga is a surface mount, dynamic LED luminaire that brings brightness to any room. It instantly alters the emotional experience of a space. By dynamically adjusting its color temperature anywhere between cold white (6500K) to warm white (2700K), you can transform the ambience of a room and promote the circadian alignment.

The BrainLit Saga luminaire embraces the black body curve with exceptional color rendering while dimming smoothly down to 0.1%.

AREAS OF USE (examples)


Office	High Value Offices / High Risk Offices / Meetings & Seminar Rooms
Industrial	High Risk Operations / Control Rooms
Education	Conference Centres / Class Rooms
Hospitality	Customer Interaction Centres / Receptions / Terminals / Lounges / Premium Room Settings / Conference Centres
Healthcare	Surgical Theaters / Sterile Processing Dep. / Intensive Care Units
Residential	Nursing Homes / Elderly Care / Luxury Room Settings

MEASUREMENTS / PACKAGING

Weight (kg)	4,3
Size LxWxH (mm)	NAxNAX120
Diameter (mm)	600
Box quantity	1
Boxed size LxWxH (mm)	660x660x160
Boxed weight (kg)	5

MARKET AVAILABILITY

EMEA EU



Driver size LxWxH (mm): 154x78x31



PRODUCT TECHNICAL SPECIFICATION

LIGHT PROPERTIES

Light source type	LED
LED color temperature	6500K-2700K
Color rendering	CRI/Ra >90
Lumen output	3400lm
mDER range	45%-96%
Beam angle	110°
Dimming range	0,1% - 100 %
Flicker handling	$P_{st}^{LM} \leq 1$, SVM $\leq 0,4$, IEEE 1789 comp.
Lifetime	0,87 (LLMF 50 000h)
	>100 000h (L70B50)

POWER PROPERTIES

Rated input power	52 W
Efficacy*	75 lm/W
Supply voltage range	120-250V
Supply power frequency	50/60Hz
Maximum circuit breaker loading (no of luminaires):	B10 B13 B16 C10 C13 C16 @230V 43 56 69 43 56 69
DALI device type	6
DALI-2 compliant	Yes
Power supply and DALI connector	WAGO WINSTA® 0,5m


MECHANICAL PROPERTIES

Colors	White matte (RAL 9003)
Material	Aluminum + PMMA
Configuration	Backlit
Mounting	Pendant
IP rating	20
Certifications	CE
Warranty	5 years


*At maximum intensity and CCT

TYPICAL CHARACTERIZATION DATA


Light distribution




Beam description



Color rendering TM-30



Color rendering CRI, (CIE 1931)



This document contains information that is subject to change without notice. This document is solely intended for, and may only be used for, the purpose of providing luminaire products to the BrainLit BioCentric Lighting System. The performance indications for BrainLit products set forth in this document are based on, and conditioned on, the products being used solely in the BrainLit BioCentric Lighting System. However, this document shall not be deemed a product warranty, whether express or implied. The BrainLit product warranty is solely contained in the purchase agreement with each customer. This document is subject to BrainLit AB's copyright. No part of this document may be reproduced or transmitted in any form or by any means, or shared with any third party, without the prior written approval of BrainLit AB. BrainLit products may be protected by one or more patents and by copyright and design rights. "BrainLit" and "BioCentric Lighting" are registered trade marks of BrainLit AB. This document does not confer upon the recipient a license to any of BrainLit intellectual property rights.