

PRODUCT SPECIFICATION

VIDAR Surface mount 60

Article no: 100027



SOLUTION DESCRIPTION

PRODUCT DESCRIPTION


The BrainLit Vidar is a 24/7 Tunable white surface mount, LED luminaire that brings brightness and provides the right light daytime as well as night time. By dynamically adjusting its color temperature anywhere between cold white (6500K) and blue deprived warm white (1800K), you can transform the ambience of a room and promote the circadian alignment in the right way whether used during day- or night time. The BrainLit Vidar luminaire embraces the black body curve with exceptional color rendering while dimming smoothly down to 10%. Similarly when used at night the low temperature white ensures comfortable blue deprived light to relax or work in.

AREAS OF USE (examples)

Office	High Value Offices / High Risk Offices / Meetings & Seminar Rooms
Industrial	High Value Manufacturing / High Risk Operations / Control Rooms
Education	Conference Centres / Class Rooms
Hospitality	Customer Interaction Centres / Receptions / Conference Rooms / Premium Room Settings / Terminals / Lounges
Healthcare	Surgical Theaters / Sterile Processing Dep. / Intensive Care Units / Wards-Long Term Care / Dialysis Centres
Residential	Nursing Homes / Elderly Care / Luxury

MEASUREMENTS / PACKAGING

Weight (kg)	5,1
Size LxWxH (mm)	NAxNAx84,2
Diameter (mm)	600
Box quantity	1
Boxed size LxWxH (mm)	660x660x140
Boxed weight (kg)	6,7
UGR 4H 8H	22,5



Driver size LxWxH (mm): 155x80x30

MARKET AVAILABILITY

EMEA	EU
------	----



PRODUCT TECHNICAL SPECIFICATION

LIGHT PROPERTIES

Light source type	LED
LED color temperature	6500K-1800K
Color rendering	CRI/Ra >90
Lumen output	6800lm
mDER range	26%-95%
Beam angle	116°
Dimming range	10%-100 %
Flicker handling	$P_{st}^{LM} \leq 1$, SVM $\leq 0,4$, IEEE 1789 comp.
Lifetime	0,88 LLMF (50 000h)
	>100 000h (L70B50)

POWER PROPERTIES

Rated input power	56W
Efficacy*	121 lm/W
Supply voltage range	220-240V
Supply power frequency	50/60Hz
Maximum circuit breaker loading (no of luminaires):	B10 B13 B16 C10 C13 C16 @230V 43 56 69 43 56 69
DALI device type	8
DALI-2 compliant	Yes
Power supply and DALI connector	WAGO WINSTA® 0,5m


MECHANICAL PROPERTIES

Colors	White matte (RAL 9003)
Material	Aluminum
Configuration	Backlit
Mounting	Surface mount (pendant P/N 100045)
IP rating	20
Certifications	CE
Warranty	5 years


*At maximum intensity and CCT

TYPICAL CHARACTERIZATION DATA


Light distribution



Beam description




Color rendering TM-30



Color rendering CRI, (CIE 1931)

CRI: 96,6 (R1-R8)



This document contains information that is subject to change without notice. This document is solely intended for, and may only be used for, the purpose of providing luminaire products to the BrainLit BioCentric Lighting System. The performance indications for BrainLit products set forth in this document are based on, and conditioned on, the products being used solely in the BrainLit BioCentric Lighting System. However, this document shall not be deemed a product warranty, whether express or implied. The BrainLit product warranty is solely contained in the purchase agreement with each customer. This document is subject to BrainLit AB's copyright. No part of this document may be reproduced or transmitted in any form or by any means, or shared with any third party, without the prior written approval of BrainLit AB. BrainLit products may be protected by one or more patents and by copyright and design rights. "BrainLit" and "BioCentric Lighting" are registered trade marks of BrainLit AB. This document does not confer upon the recipient a license to any of BrainLit intellectual property rights.